

CLAIMS

4. A device as claimed in claim 3, in which at least one of the base element (6) and the engaging element (7) of each tool (5) supports a rib (12), which is arranged to engage the material web (3) in the closed position of the tool (5).

5. A device as claimed in claim 4, in which said rib (12) of each tool (5) has an extent that corresponds to the extent of the connecting portion (11) of a container blank (2).

5

6. A device as claimed in claim 4 or 5, in which said rib (12) is supported by an arrangement involving springs (38), which when moving the tool (5) to said closed position are arranged for a given compression.

10

7. A device as claimed in any one of the preceding claims, in which each tool (5) is arranged to provide said joining by heat sealing.

15

8. A device as claimed in any one of the preceding claims, further comprising a control means (18) which is arranged to engage said tool (5) with, and disengage the same from, the material web (3).

20

9. A device as claimed in claim 8, in which the control means (18) comprises a link mechanism (20) for each of the tools (5) and a stationary cam structure (19), each tool (5) being connected to the cam structure (19) by said link mechanism (20) and the cam structure (16) being arranged, during rotation of the tool holder (4), to control each tool (5) to be closed and opened, respectively.

25

10. A device as claimed in claim 8, in which each
30 link mechanism (20) comprises an articulated link arm
(25) which is arranged in an over-centred position.

30

11. A device as claimed in claim 9 or 10 when referring back to claim 6, in which each link mechanism (20) comprises a roll (23) which is held in a cam groove (24) of the cam structure (19), a sensor being arranged in the cam groove (24) for sensing the force by which the roll

35

(23) abuts against a bearing surface of the cam groove
(24).

12. A device as claimed in any one of the preceding
5 claims, in which the tool holder (4) is rotatably mounted
on one side.

13. A device as claimed in any one of the preceding claims, further comprising a punching station (10), which is arranged downstream of the tool holder (4) and arranged to punch container blanks (5) along said connecting portions (11).

14. A device as claimed in claim 13, in which said
15 punching station (10) is arranged for such punching that
a succession of container blanks (2) are connected to
each other to form a continuous web (17) of container
blanks (2).

20 15. A device as claimed in any one of the preceding
claims, in which the tool holder (4) in operation is
arranged for continuous rotation.

16. A device as claimed in any one of the preceding
25 claims, further comprising a registering mechanism (13)
positioned upstream of the tool holder (4) and adapted
to sense the tension in the material web (3) and to
adjust said tension according to a predetermined value.

30 17. A method for producing container blanks (2) from
a material web (3) by joining opposite wall portions of
the material web (3) along connecting portions (11), com-
prising

deflecting said material web (3) over a tool holder
35 (4),

rotating the tool holder (4) to move tools (5) supported by the same along a working path (WP), and

by continued rotation of the tool holder (4), moving the tools (5) along a return path (RP) to the beginning of said working path (WP),

each tool, for providing said joining, being engaged
5 with the material web (5) and moved together with said material web (3) during the movement of the tool (5) along said working path (WP).

18. A method as claimed in claim 17, wherein the
10 material web (3) is folded to a web folded longitudinally in the form of a W.

19. A method as claimed in claim 17 or 18, wherein each tool (5) is engaged with the material web (3) by
15 pivoting an engaging element (7) downwards to a base element (6) for clamping the material web (3) therebetween.

20. A method as claimed in any one of claims 17-19, in which said tool holder (4) is rotated continuously to
20 provide continuous production of container blanks (2).

21. A method as claimed in any one of claims 17-19, in which the tool holder (4) is rotated in an indexing motion.

25